

MARK SCHEME for the October/November 2012 series

9702 PHYSICS

9702/43

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2012 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.

Page 2	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	43

Section A

- 1 (a) (i) number of molecules B1 [1]
- (ii) mean square speed B1 [1]
- (b) (i) 1. $pV = nRT$
 $n = (6.1 \times 10^5 \times 2.1 \times 10^4 \times 10^{-6}) / (8.31 \times 285)$
 $n = 5.4 \text{ mol}$ C1
C1
A1 [3]
2. either $N = nN_A$
 $= 5.4 \times 6.02 \times 10^{23}$
 $= 3.26 \times 10^{24}$ C1
A1
or
 $pV = NkT$
 $N = (6.1 \times 10^5 \times 2.1 \times 10^4 \times 10^{-6}) / (1.38 \times 10^{-23} \times 285)$ (C1)
 $N = 3.26 \times 10^{24}$ (A1) [2]
- (ii) either $6.1 \times 10^5 \times 2.1 \times 10^{-2} = \frac{1}{3} \times 3.25 \times 10^{24} \times 4 \times 1.66 \times 10^{-27} \times \langle c^2 \rangle$ C1
 $\langle c^2 \rangle = 1.78 \times 10^6$ C1
 $c_{\text{RMS}} = 1.33 \times 10^3 \text{ m s}^{-1}$ A1
or
 $\frac{1}{2} \times 4 \times 1.66 \times 10^{-27} \times \langle c^2 \rangle = \frac{3}{2} \times 1.38 \times 10^{-23} \times 285$ (C1)
 $\langle c^2 \rangle = 1.78 \times 10^6$ (C1)
 $c_{\text{RMS}} = 1.33 \times 10^3 \text{ m s}^{-1}$ (A1) [3]
- 2 (a) (i) 1. 0.1 s, 0.3 s, 0.5 s, etc (*any two*) A1 [1]
2. either 0, 0.4 s, 0.8 s, 1.2 s
or
0.2 s, 0.6 s, 1.0 s (*any two*) A1 [1]
- (ii) period = 0.4 s C1
frequency = (1/0.4 =) 2.5 Hz A1 [2]
- (iii) phase difference = 90° or $\frac{1}{2} \pi$ rad B1 [1]
- (b) frequency = 2.4 – 2.5 Hz B1 [1]
- (c) e.g. attach sheet of card to trolley M1
increases damping / frictional force A1
e.g. reduce oscillator amplitude (M1)
reduces power/energy input to system (A1) [2]

Page 3	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	43

- 3 (a) (i) (tangent to line gives) direction of force on a (small test) mass B1 [1]
- (ii) (tangent to line gives) direction of force on a (small test) charge
charge is positive M1
A1 [2]
- (b) similarity:
e.g. radial fields
lines normal to surface
greater separation of lines with increased distance from sphere
field strength $\propto 1 / (\text{distance to centre of sphere})^2$
(allow any sensible answer) B1
- difference:
e.g. gravitational force (always) towards sphere B1
electric force direction depends on sign of charge on sphere / towards or
away from sphere B1
e.g. gravitational field/force is attractive (B1)
electric field/force is attractive or repulsive (B1)
(allow any sensible comparison) [3]
- (c) gravitational force = $1.67 \times 10^{-27} \times 9.81$
 $= 1.6 \times 10^{-26} \text{ N}$ A1
electric force = $1.6 \times 10^{-19} \times 270 / (1.8 \times 10^{-2})$ C1
 $= 2.4 \times 10^{-15} \text{ N}$ A1
electric force very much greater than gravitational force B1 [4]
- 4 (a) force on proton is normal to velocity and field
provides centripetal force (for circular motion) M1
A1 [2]
- (b) magnetic force = Bqv B1
centripetal force = $mr\omega^2$ or mv^2/r B1
 $v = r\omega$ B1
 $Bqv = Bqr\omega = mr\omega^2$
 $\omega = Bq/m$ A1 [4]
- 5 (a) either $\phi = BA \sin \theta$ M1
where A is the area (through which flux passes)
 θ is the angle between B and (plane of) A A1
or
 $\phi = BA$ (M1)
where A is area normal to B (A1) [2]
- (b) graph: V_H constant and non zero between the poles and zero outside
sharp increase/decrease at ends of magnet M1
A1 [2]

Page 4	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	43

- (c) (i) (induced) e.m.f. proportional to rate of change of (magnetic) flux (linkage) M1 A1 [2]
- (ii) short pulse on entering and on leaving region between poles pulses approximately the same shape but opposite polarities e.m.f. zero between poles and outside M1 A1 A1 [3]
- 6 (a) (i) connection to 'top' of resistor labelled as positive B1 [1]
- (ii) diode B and diode D B1 [1]
- (b) (i) $V_P = 4.0\text{V}$
mean power = $V_P^2/2R$
= $4^2 / (2 \times 2700)$
= $2.96 \times 10^{-3}\text{W}$ C1 C1 A1 [3]
- (ii) capacitor, correct symbol, connected in parallel with R B1 [1]
- (c) graph: half-wave rectification same period and same peak value M1 A1 [2]
- 7 (a) wavelength associated with a particle that is moving M1 A1 [2]
- (b) (i) kinetic energy = $1.6 \times 10^{-19} \times 4700$
= $7.52 \times 10^{-16}\text{J}$ C1
either energy = $p^2/2m$ or $E_K = \frac{1}{2}mv^2$ and $p = mv$ C1
 $p = \sqrt{(7.52 \times 10^{-16} \times 2 \times 9.1 \times 10^{-31})}$ C1
= $3.7 \times 10^{-23}\text{Ns}$
 $\lambda = h/p$ C1
= $(6.63 \times 10^{-34}) / (3.7 \times 10^{-23})$
= $1.8 \times 10^{-11}\text{m}$ A1 [5]
- (ii) wavelength is about separation of atoms can be used in (electron) diffraction B1 B1 [2]
- 8 (a) (i) $x = 2$ A1 [1]
- (ii) *either* beta particle or electron B1 [1]
- (b) (i) mass of separate nucleons = $\{(92 \times 1.007) + (143 \times 1.009)\} \text{u}$
= 236.931u C1 C1
binding energy = $236.931 \text{u} - 235.123 \text{u}$
= 1.808u A1 [3]

Page 5	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	43

(ii) $E = mc^2$
energy = $1.808 \times 1.66 \times 10^{-27} \times (3.0 \times 10^8)^2$
= $2.7 \times 10^{-10} \text{ J}$
binding energy per nucleon = $(2.7 \times 10^{-10}) / (235 \times 1.6 \times 10^{-13})$
= 7.18 MeV

C1
C1
M1
A0 [3]

(c) energy released = $(95 \times 8.09) + (139 \times 7.92) - (235 \times 7.18)$
= 1869.43 – 1687.3
= 182 MeV
(allow calculation using mass difference between products and reactants)

C1
A1 [2]

Section B

9 (a) light-emitting diode (allow LED) B1 [1]

(b) gives a high or a low output / +5 V or –5 V output
dependent on which of the inputs is at a higher potential M1
A1 [2]

(c) (i) provides a reference/constant potential B1 [1]

(ii) determines temperature of 'switch-over' B1 [1]

(d) (i) relay A1 [1]

(ii) relay connected correctly for op-amp output and high-voltage circuit
diode with correct polarity in output from op-amp B1
B1 [2]

10 (a) background reading = 19 B1 [1]

(b) A = 2 A1
B = 5 A1
C = 9 A1
D = 3 A1 [4]
(Allow 1 mark if only subtracts background reading)

(c) (i) either 5, 14 or 14, 5 (A+D, B+C or v.v.) B1 [1]

(ii) Three numbers and 'inside' number is 8 (B+D) B1
Three numbers and 'outside' numbers are either 2,9 or 9,2 (A,C or v.v.) B1 [2]

11 (a) high frequency wave B1
the amplitude or the frequency is varied M1
the variation represents the information signal /
in synchrony with (the displacement of) the information signal. A1 [3]

Page 6	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	43

- (b) e.g. shorter aerial required
 longer transmission range / lower transmitter power / less attenuation
 allows more than one station in a region
 less distortion
 (allow any three sensible suggestions, 1 mark each)

B3 [3]

12 (a) (i) e.g. linking a (land) telephone to the (local) exchange

B1 [1]

(ii) e.g. connecting an aerial to a television

B1 [1]

(iii) e.g. linking a ground station to a satellite

B1 [1]

(b) (i) attenuation = $10 \lg (P_2 / P_1)$

C1

total attenuation = $2.1 \times 40 (= 84 \text{ dB})$

C1

$84 = 10 \lg (\{450 \times 10^{-3}\} / P)$

$P = 1.8 \times 10^{-9} \text{ W}$

A1 [3]

(answer $1.1 \times 10^8 \text{ W}$ scores 1 mark only)

(ii) maximum attenuation = $10 \lg (\{450 \times 10^{-3}\} / \{7.2 \times 10^{-11}\})$
 = 98 dB

C1

maximum length = $98/2.1$

= 47 km

A1 [2]