

CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the October/November 2014 series

9702 PHYSICS

9702/43

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2014 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

® IGCSE is the registered trademark of Cambridge International Examinations.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	43

- 1 (a) (i) *either* $\omega = 2\pi/T$ or $\omega = 2\pi f$ and $f = 1/T$ C1
 $\omega = 2\pi/0.30$
 $= 20.9 \text{ rad s}^{-1}$ (accept 2 s.f.) A1 [2]
- (ii) kinetic energy $= \frac{1}{2}m\omega^2x_0^2$ or $v = \omega x_0$ and $\frac{1}{2}mv^2$ C1
 $= \frac{1}{2} \times 0.130 \times 20.9^2 \times (1.5 \times 10^{-2})^2 = 6.4 \times 10^{-3} \text{ J}$ A1 [2]
- (b) (i) as magnet moves, flux is cut by cup/aluminium giving rise to induced e.m.f. (in cup) B1
induced e.m.f. gives rise to currents and heating of the cup B1
thermal energy derived from oscillations of magnet so amplitude decreases B1
or
induced e.m.f. gives rise to currents which generate a magnetic field (B1)
the magnetic field opposes the motion of the magnet so amplitude decreases (B1) [3]
- (ii) *either* use of $\frac{1}{2}m\omega^2x_0^2$ and $x_0 = 0.75 \text{ cm}$ or x_0 is halved so $\frac{1}{4}$ energy C1
to give new energy = 1.6 mJ
either loss in energy = $6.4 - 1.6$ or loss = $\frac{3}{4} \times 6.4$ giving loss = 4.8 mJ A1 [2]
- (c) $q = mc\Delta\theta$
 $4.8 \times 10^{-3} = 6.2 \times 10^{-3} \times 910 \times \Delta\theta$ C1
 $\Delta\theta = 8.5 \times 10^{-4} \text{ K}$ A1 [2]
- 2 (a) smooth curve with decreasing gradient, not starting at $x = 0$ M1
end of line not at $g = 0$ or horizontal A1 [2]
- (b) straight line with positive gradient M1
line starts at origin A1 [2]
- (c) sinusoidal shape B1
only positive values and peak/trough height constant B1
4 'loops' B1 [3]
- 3 (a) initially, $pV/T = (2.40 \times 10^5 \times 5.00 \times 10^{-4})/288 = 0.417$ M1
finally, $pV/T = (2.40 \times 10^5 \times 14.5 \times 10^{-4})/835 = 0.417$ M1
ideal gas because pV/T is constant A1 [3]
(allow 2 marks for two determinations of V/T and then 1 mark for V/T and p constant, so ideal)

Page 3	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	43

- (b) (i) work done = $p\Delta V$
 $= 2.40 \times 10^5 \times (14.5 - 5.00) \times 10^{-4}$
 $= 228 \text{ J (ignore sign, not 2 s.f.)}$ C1
A1 [2]
- (ii) $\Delta U = q + w = 569 - 228$
 $= 341 \text{ J}$ M1
increase A1 [2]
- 4 (a) acceleration / force proportional to displacement (from a fixed point)
either acceleration and displacement in opposite directions
or acceleration always directed towards a fixed point M1
A1 [2]
- (b) (i) zero & 0.625 s or 0.625 s & 1.25 s or 1.25 s & 1.875 s or 1.875 s & 2.5 s A1 [1]
- (ii) 1. $\omega = 2\pi / T$ and $v_0 = \omega x_0$ C1
 $\omega = 2\pi / 1.25$
 $= 5.03 \text{ rad s}^{-1}$ C1
- $v_0 = 5.03 \times 3.2$
 $= 16.1 \text{ cm s}^{-1}$ (allow 2 s.f.) A1 [3]
2. $v = \omega\sqrt{(x_0^2 - x^2)}$
either $\frac{1}{2}\omega a = \omega\sqrt{(x_0^2 - x^2)}$ or $\frac{1}{2} \times 16.1 = 5.03\sqrt{(3.2^2 - x^2)}$ C1
 $x_0^2 / 4 = x_0^2 - x^2$ $2.58 = 3.2^2 - x^2$
 $x = 2.8 \text{ cm}$ $x = 2.8 \text{ cm}$ A1 [2]
- (c) sketch: loop with origin at its centre M1
correct intercepts & shape based on (b)(ii) A1 [2]
- 5 (a) work done / energy in moving unit positive charge
from infinity (to the point) M1
A1 [2]
- (b) (i) $V = q / 4\pi\epsilon_0 r$
at 16 kV, $q = 3.0 \times 10^{-8} \text{ C}$
- $r = (3.0 \times 10^{-8}) / (4\pi \times 8.85 \times 10^{-12} \times 16 \times 10^3)$ C1
 $= 1.69 \times 10^{-2} \text{ m (allow 2 s.f.)}$ A1 [2]
(allow any answer which rounds to 1.7×10^{-2})
- (ii) energy is / represented by area 'below' line C1
energy = $\frac{1}{2}qV$
 $= \frac{1}{2} \times 24 \times 10^3 \times 4.5 \times 10^{-8}$ C1
 $= 5.4 \times 10^{-4} \text{ J}$ A1 [3]
- (c) $V = q / 4\pi\epsilon_0 r$ and $E = q / 4\pi\epsilon_0 r^2$ giving $Er = V$ B1
 $2.0 \times 10^6 \times 1.7 \times 10^{-2} = V$ C1
 $V = 3.4 \times 10^4 \text{ V}$ A1 [3]

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	43

- 6 (a) for the two capacitors in parallel, capacitance = 96 μF
for complete arrangement, $1/C_T = 1/96 + 1/48$
 $C_T = 32 \mu\text{F}$ C1
A1 [2]
- (b) p.d. across parallel combination is one half p.d. across single capacitor
total p.d. = 9V C1
A1 [2]
- 7 (a) *either* charge exists in discrete and equal quantities
or multiples of elementary charge / $e / 1.6 \times 10^{-19} \text{ C}$ B1 [1]
- (b) (i) force due to magnetic field must be upwards
B-field into the plane of the paper B1
B1 [2]
- (ii) sketch showing: deflection consistent with force in (b)(i)
reasonable curve B1
B1 [2]
- 8 (a) discrete amount / packet / quantum of energy
of electromagnetic radiation / EM radiation M1
A1 [2]
- (b) (i) $E = hc/\lambda$
 $= (6.63 \times 10^{-34} \times 3.0 \times 10^8) / (570 \times 10^{-9}) = 3.49 \times 10^{-19} \text{ J}$ A1 [1]
- (ii) 1. number = $(2.7 \times 10^{-3}) / (3.5 \times 10^{-19})$
 $= 7.7 \times 10^{15}$ C1
A1 [2]
2. momentum of photon = h/λ
 $= (6.63 \times 10^{-34}) / (570 \times 10^{-9})$
 $= 1.16 \times 10^{-27} \text{ kg m s}^{-1}$ C1
C1
- change in momentum = $1.16 \times 10^{-27} \times 7.7 \times 10^{15}$
 $= 8.96 \times 10^{-12} \text{ kg m s}^{-1}$ A1 [3]
- (allow $E = pc$ route to 9×10^{-12})
- (c) pressure = (change in momentum per second) / area C1
 $= (8.96 \times 10^{-12}) / (1.3 \times 10^{-5})$
 $= 6.9 \times 10^{-7} \text{ Pa}$ A1 [2]
- 9 (a) activity = $(1.7 \times 10^{14}) / (2.5 \times 10^6)$
 $= 6.8 \times 10^7 \text{ Bq kg}^{-1}$ A1 [1]
- (b) (i) energy released per second in 1.0 kg of steel
 $= 6.8 \times 10^7 \times 0.067 \times 1.6 \times 10^{-13}$
 $= 7.3 \times 10^{-7} \text{ J}$ B1 [1]

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	43

(ii) this is a very small quantity of energy so steel will not be warm B1 [1]

(iii) $A = A_0 e^{-\lambda t}$ and $\lambda t_{1/2} = \ln 2$ C1
 $400 = (6.8 \times 10^7) \exp(-[\ln 2 \times t]/92)$ C1
 $t = 1600$ years A1

or

$A = A_0 / 2^n$ (C1)
 $n = 17.4$ (C1)
 $t = 17.4 \times 92 = 1600$ years (A1) [3]

Section B

10 (a) (i) thermistor/thermocouple B1 [1]

(ii) quartz crystal/piezoelectric crystal or transducer/microphone B1 [1]

(b) (i) $V_{OUT} = -5V$ A1
 inverting input is positive or V_- is positive or $V_- > V_+$ so V_{OUT} is negative B1
 op-amp has very large/infinite gain and so saturates B1 [3]

(ii) sketch: V_{OUT} switches from (+) to (-) when V_{IN} is zero B1
 V_{OUT} is +5V or -5V M1
 V_{OUT} is negative when V_{IN} is positive (or v.v.) A1 [3]

11 (a) product of density and speed M1
 density of medium, speed of wave in medium A1 [2]
 (not "speed of light", 0/2)

(b) (i) $\alpha = (6.4 - 1.7)^2 / (6.4 + 1.7)^2$ C1
 $= 0.34$ A1 [2]

(ii) $I/I_0 = e^{-\mu x}$ C1
 $= \exp(-23 \times 3.4 \times 10^{-2})$ C1
 $= 0.46$ A1 [3]

(iii) $I_R/I = (0.46)^2 \times 0.34$ C1
 $= 0.072$ A1 [2]

12 (a) analogue: continuously variable B1
 digital: two/distinct levels only or 1 s and 0 s or highs and lows B1 [2]

(b) (i) 5 A1 [1]

(ii) 1 1 0 1 A1 [1]

Page 6	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	43

- (c) greater number of voltage/signal levels
 smaller step heights in reproduced signal
 smaller voltage/signal changes can be seen
 B1
 B1
 B1 [3]
- 13 (a) same carrier frequencies can be re-used
 but not in neighbouring cells/possible to use more handsets
 M1
 A1 [2]
- (b) e.g. wavelength is short
 so aerial on mobile phone conveniently short
 (M1)
 (A1)
- e.g. limited range
 so low power/less interference between cells
 (M1)
 (A1)
- e.g. large number of channels/greater bandwidth
 so more simultaneous callers
 (M1)
 (A1) [4]